

LASHING WIRE

61000, 61010, 61020, 61030, 61040 SERIES

The difference between DCD Lashing Wire and other lashing wires isn't visible to the eye. While all lashing wires may look and feel alike, DCD lashing wire is specially annealed for extra durability where the lash meets the strand.

Wound in continuous coils for easy payout, DCD lashing wires won't come back to haunt you. Instead, the lash holds tight and stays even. DCD gives you 14 choices of size and types: Aluminum, galvanized, various grades of stainless and non-metallic. All come in popular sizes to match any job, and while our sizes and types vary, our quality doesn't.



STRAIGHT HUB: Industry standard coils (5-1/2") to fit the DCD Lineman and Eagle lashers, and other lashers with drop-down doors.

TAPERED HUB: Standard outside diameter to fit a tapered Cable Spinning Equipment hub (eg, D lashers).

DISPOSABLE METAL REELS: Pre-coiled on 6" aluminum reels, to fit legacy CSE lashers with a 1-1/4" mounting post. (CSE K & Special K lashers).

Q-SIZED: Compact coils (4" diameter) to fit the DCD Model Q hand lasher.

NON-METALLIC MATERIAL: Two sizes, one for industry-standard straight hub lashers like the Lineman; a second, high-capacity spool to fit modified DD lashers. Note: a lasher tension adjustment mechanism is necessary to compensate for the softer aramid strand.

LASHING WIRE SPECIFICATIONS

Lasher	Part No.	Model	Wire Dia.	Material	Coils/box	Length	Net Box Weight	Total Coil Weight
Straight Hub								
Lineman, Eagle, S, K, Special K	61010-040	12A-3A	0.091"	GALVANIZED	6	325 FT	45 LB	7.19 LB
	61010-050	13A-3A	0.045"	430 STAINLESS	6	1,200 FT	41 LB	6.56 LB
	61010-070	26A-3A	0.045"	316 STAINLESS	6	1,200 FT	42 LB	6.69 LB
	61010-080	27A-3A	0.045"	302 STAINLESS	6	1,200 FT	42 LB	6.69 LB
Tapered Hub								
	61000-050	13A-1A	0.045"	430 STAINLESS	6	1,200 FT	41 LB	6.56 LB
Disposable Metal Reels								
Legacy K & Special K	61020-010	7AK-1AK	0.091"	ALUMINUM	5	350 FT	19 LB	3.31 LB
	61020-020	10AK-1AK	0.061"	316 STAINLESS	5	750 FT	43 LB	8.34 LB
	61020-030	11AK-1AK	0.061"	430 STAINLESS	5	750 FT	42 LB	8.19 LB
	61020-050	13AK-1AK	0.045"	430 STAINLESS	5	1,400 FT	43 LB	8.31 LB
	61020-060	23ANM-1AK	N/A	NON-METALLIC	5	1,200 FT	11 LB	1.87 LB
Special								
Q	61030-010	10AS-1AS	0.061"	316 STAINLESS	8	225 FT	20 LB	2.30 LB
	61030-020	11AS-1AS	0.061"	430 STAINLESS	8	225 FT	20 LB	2.26 LB
	61030-030	13AS-1AS	0.045"	430 STAINLESS	8	375 FT	18 LB	2.05 LB
Non-Metallic Material								
Straight-hub & modified DD	61040-010	23ANM-3A	N/A	NON-METALLIC	6	1,000 FT	9 LB	1.01 LB
	61040-020	23ANM-4000	N/A	NON-METALLIC	1	4,000 FT	5 LB	4.04 LB

Web Site: www.dcdesign.com



Toll Free: 1-888-SWIVELS (794-8357)

Tel: 604-232-4445

Fax: 604-232-4446

E-mail: sales@dcdesign.com

OVERHEAD PRODUCTS

DCD