

MINI-GRIP™


24500 SERIES

The Mini-Grip™ pulling eye is re-usable and has a lug style head that will attach directly into a line swivel or other type of connector. This pulling eye has 3 set screws that clamp directly onto the cable conductor. It is suitable for smaller cables with conductors having 7 strands or less.



Note that these pulling eyes should always be used with a line swivel, series 00505.

For 7 Strand or Less Power Cable				
Part No.	Max Cable Size	Max. Core Dia.	Body Dia.	Weight
24500-343	4 - 3 AWG	0.33"	3/4"	0.30 LB
24500-406	2 - 1/0 AWG	0.39"	7/8"	0.37 LB
24500-562	2/0 - 4/0 AWG	0.55"	1"	0.44 LB



PULLING HARNESS

25000 SERIES

The purpose of this product is to allow single or multiple pulls at one time by attaching 1 or 2 cables to the one pulling harness. The harness legs are manufactured from aircraft quality galvanized wire rope while the connector end is manufactured from stainless steel.



The two leg units are staggered in length so the individual connections are not interfering with each other. The safety factor is based on equal pull on both legs.

The double leg harness is available in long or short configurations and each is supplied with 1 hex key and 4 set screws. The single harness is supplied with 1 hex key and 2 set screws. Both the hex key and the set screws are available separately.

Cable sizes that can be pulled with these harnesses are 2/0 to 4/0 AWG.

Part No.	Description	Wire Dia.	No. of Legs	3:1 Safe Working Load		Weight
				Leg Capacity	Total Capacity	
25000-010	SINGLE LEG	1/4"	1	2,300 LB	2,300 LB	1.00 LB
25000-020	DOUBLE LEG - SHORT	1/4"	2	2,300 LB	4,600 LB	1.70 LB
25000-021	DOUBLE LEG - LONG	1/4"	2	2,300 LB	4,600 LB	2.00 LB
90000-166	SET SCREW	-	-	-	-	0.10 LB
00101-375	HEX KEY	-	-	-	-	0.28 LB

