

# LUBE SPREADER

## 00510 series

This product is designed to spread the DCD TUBE-LUBE® 346 around the walls and along the length of the duct, while also acting as a connector.

The body is constructed out of Stainless Steel and the polyurethane disc has angular grooves which allow better distribution of lubricant.



**TABLE A: Spreader Disc**

Spreader Disc Part No.	Disc Dia.	Weight	Connector Body
00515-100	1-1/16"	0.012 lb.	00510-010
00515-125	1-3/16"	0.015 lb.	00510-010
00515-150	1-5/16"	0.022 lb.	00510-010
00515-175	1-7/16"	0.026 lb.	00510-010
00515-200	1-7/8"	0.045 lb.	00510-025
00515-250	2-3/16"	0.066 lb.	00510-025
00515-300	2-13/16"	0.110 lb.	00510-025
00515-350	3-1/4"	0.170 lb.	00510-035
00515-400	3-3/4"	0.240 lb.	00510-035
00515-500	4-11/16"	0.450 lb.	00510-035
00515-680	5-1/2"	0.640 lb.	00510-035
00515-640	5-13/16"	0.670 lb.	00510-035

How to Order:

1. Select disc from Table A to fit the internal diameter of conduit to be lubricated.
2. Select Connector Body from Table B to match selected disc from Table A.

**Table B: Connector Body**

Connector Part No.	*Safe Working Load	Body Dia.	Overall Length	Weight	Clevis Pin
00510-010	1,500 lb.	7/8"	3-3/16"	0.25 lb.	00010-SLT
00510-025	4,000 lb.	1-3/8"	4-5/8"	0.70 lb.	00025-HEX
00510-035	7,200 lb.	2"	6-1/4"	2.50 lb.	00035-HEX

\*Safety factor is 3:1



Web Site: [www.dcdesign.com](http://www.dcdesign.com)  
E-mail: [sales@dcdesign.com](mailto:sales@dcdesign.com)

Toll Free: 1-888-SWIVELS (794-8357)  
Tel: 604-232-4445  
Fax: 604-232-4446

CABLE PULLING LUBRICANTS

