

DUCT PULLERS

00650/00651 series

These products are designed to install Polyethylene Ducting using expanding jaws to grip the inside diameter of the duct while the outside diameter is prevented from stretching by a permanent outer sleeve on the Puller. The outer sleeve also provides a complete seal around the ducting preventing any fluids or contaminants from entering either the duct or the Pulling Eye.

The pulling head is manufactured from alloy steel and is designed to protect the mechanism from heavy knocks or side loads. It is also fully sealed to prevent any fluid entry.

Care should be taken at all times not to exceed the yield value of the ducting since this may cause permanent deformation to the duct as well as loss to the integrity of the polyethylene.

These Duct Pullers are installed quickly and easily and require no special tooling. A new tooth profile makes removal much easier than the earlier models.

Duct wall thickness is normally designated by an SDR value. The lower the SDR value, the heavier the wall thickness. These products can be used on SDR 9 through SDR 17 ducting and Schedule 40.



Duct Puller Part No.	Nominal Duct Dia.	Min. Duct Inside Dia.	Max. Duct Inside Dia.	Max. Duct Outside Dia.	Weight
00650-125	1-1/4"	1-1/4"	1-1/2"	1-21/32"	1.5 lb.
00650-150	1-1/2"	1-7/16"	1-11/16"	1-29/32"	1.5 lb.
00650-200	2"	1-13/16"	2-3/16"	2-3/8"	3.5 lb.
00650-250	2-1/2"	2-3/16"	2-9/16"	2-7/8"	5.0 lb.
00650-300	3"	2-11/16"	3-1/16"	3-1/2"	7.0 lb.
00650-400	4"	3-7/16"	4-1/4"	4-1/2"	17.0 lb.
00650-500	5"	4-5/16"	5-1/8"	5-9/16"	26.0 lb.
00650-600	6"	5-1/16"	6-1/16"	6-5/8"	50.0 lb.

Duct Puller Part No.	Nominal Duct Dia.	Min. Duct Inside Dia.	Max. Duct Inside Dia.	Max. Duct Outside Dia.	Weight
00651-040	40 mm	32.5 mm 1-1/4"	38.1 mm 1-1/2"	40.0 mm 1-9/16"	1.5 lb.
00651-050	50 mm	36.5 mm 1-7/16"	44.1 mm 1-3/4"	50.0 mm 1-15/16"	2.0 lb.
00651-063	63 mm	50.8 mm 2"	57.1 mm 2-1/4"	63.0 mm 2-1/2"	4.0 lb.
00651-075	75 mm	60.3 mm 2-3/8"	66.7 mm 2-5/8"	75.0 mm 2-15/16"	6.0 lb.
00651-090	90 mm	73.0 mm 2-7/8"	81.0 mm 3-3/16"	90.0 mm 3-9/16"	8.0 lb.
00651-110	110 mm	85.7 mm 3-3/8"	100.0 mm 3-15/16"	110.0 mm 4-3/8"	17.5 lb.
00651-125	125 mm	98.8 mm 3-7/8"	111.5 mm 4-3/8"	125.0 mm 5"	21.0 lb.
00651-140	140 mm	114.0 mm 4-1/2"	127.0 mm 5"	140.0 mm 5-1/2"	26.0 lb.
00651-160	160 mm	125.4 mm 4-15/16"	142.9 mm 5-5/8"	160.0 mm 6-5/16"	49.0 lb.

Web Site: www.dccddesign.com
E-mail: sales@dccdesign.com

Toll Free: 1-888-SWIVELS (794-8357)
Tel: 604-232-4445
Fax: 604-232-4446

DUCT INSTALLATION & PROOFING

DCD