

QUICK LINK CONNECTOR 00660 series

The Quick Link can be used in a variety of applications to connect a number of our accessories to each other. They provide low cost, ease of use and no maintenance.

Part No.	Nominal Size	*Safe Working Load	Loop Inside Width	O/A Outside Length	Weight
00660-187	3/16"	660 lb.	1/2"	2"	0.05 lb.
00660-250	1/4"	880 lb.	1/2"	2-3/8"	0.08 lb.
00660-312	5/16"	1,760 lb.	5/8"	3"	0.18 lb.
00660-375	3/8"	2,200 lb.	11/16"	3-3/16"	0.24 lb.
00660-437	7/16"	2,600 lb.	3/4"	3-1/2"	0.32 lb.
00660-500	1/2"	3,300 lb.	7/8"	4-1/8"	0.52 lb.

*Safety factor is 2:1



WIRE ROPE BRIDLE SLING 23000 series

The purpose of this product is to allow multiple pulls at one time by attaching 2, 3 or 4 cables or ducts to the Puller. The slings are manufactured from aircraft quality wire rope. The various "legs" are staggered in length so the individual connections are not interfering with each other. The lead coupler can be easily dismantled to change out a leg or to add another leg.

Each leg is marked with load capacity and they are pull tested to 3 times that rating. The safety factor of 3:1* is based on equal pull on all cables, (horizontal pull only). Yokes and wire rope sling legs may be ordered separately. Other sling configurations are available upon request.

Sling Part No.	Wire Dia.	No. of Legs	*Leg Capacity	*Total Capacity	Weight	DCD Swivels that Fit:	
						Over Leg Loop	Over Sling Shackle
23125-020	1/8"	2	650 lb.	1,300 lb.	0.32 lb.	00505-005	00505-020
23125-030	1/8"	3	650 lb.	1,950 lb.	0.55 lb.	00505-010	00505-025
23125-040	1/8"	4	650 lb.	2,600 lb.	0.65 lb.	00505-015	00505-027
23250-020	1/4"	2	2,300 lb.	4,600 lb.	1.30 lb.	00505-010	00505-027
23250-030	1/4"	3	2,300 lb.	6,900 lb.	1.60 lb.	00505-015	00505-030
23250-040	1/4"	4	2,300 lb.	9,200 lb.	2.00 lb.	00505-020	00505-035
23375-020	3/8"	2	4,800 lb.	9,600 lb.	3.00 lb.	00505-020	00505-035
23375-030	3/8"	3	4,800 lb.	14,400 lb.	4.00 lb.	00505-025	00505-040
23375-040	3/8"	4	4,800 lb.	19,200 lb.	6.00 lb.	00505-027	00505-041
23500-020	1/2"	2	6,900 lb.	13,800 lb.	6.90 lb.	00505-030	00505-045
23500-030	1/2"	3	6,900 lb.	20,700 lb.	8.40 lb.	00505-035	00505-045
23500-040	1/2"	4	6,900 lb.	27,600 lb.	13.00 lb.		00505-050

*Safety factor is 3:1

