

PULLING GRIPS

00674 / 00675 series DOUBLE WEAVE – SINGLE EYE – SLACK GRIP – CLOSED MESH

These grips offer a Flexible Eye and Double Weave galvanized wire construction — for those times when a side loaded pulling rope is easier. If the cable end is available, then the Closed Mesh is preferred.

Part No.	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00674-010	0.38" to 0.74"	14"	2,500 lb.	0.44 lb.
00674-020	0.75" to 1.12"	17"	3,000 lb.	0.48 lb.
00674-030	1.13" to 1.49"	18"	5,000 lb.	0.84 lb.
00674-040	1.50" to 1.99"	20"	10,000 lb.	1.41 lb.
00675-050	2.00" to 2.49"	21"	11,000 lb.	2.56 lb.
00675-065	2.50" to 2.99"	22"	12,000 lb.	2.64 lb.
00675-080	3.00" to 3.74"	23"	15,000 lb.	2.95 lb.
00675-095	3.75" to 4.24"	24"	15,000 lb.	4.63 lb.



00678 / 00679 series DOUBLE WEAVE – SINGLE EYE – SLACK GRIP – SPLIT MESH (Lace-up)

These grips offer a Flexible Eye and Double Weave galvanized wire construction — for those times when a side loaded pulling rope is easier. If the cable end is not available, then the Split Mesh is preferred.

Part No.	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00678-010	0.38" to 0.74"	14"	4,100 lb.	0.44 lb.
00678-020	0.75" to 1.12"	17"	4,970 lb.	0.55 lb.
00678-030	1.13" to 1.49"	18"	8,150 lb.	0.82 lb.
00678-040	1.50" to 1.99"	20"	12,100 lb.	1.39 lb.
00679-050	2.00" to 2.49"	21"	16,140 lb.	1.92 lb.
00679-065	2.50" to 2.99"	22"	16,140 lb.	2.00 lb.
00679-080	3.00" to 3.74"	23"	20,170 lb.	2.20 lb.
00679-095	3.75" to 4.24"	24"	23,400 lb.	3.09 lb.



00680 series DOUBLE WEAVE – SINGLE EYE – SHOULDERS

These grips offer a Flexible Eye with Shoulders and Double Weave galvanized wire construction. The shoulders offer added protection to the utility being pulled in as well as protecting the leading wire strands.

Part No.	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00680-025	0.25" to 0.49"	18"	4,800 lb.	0.4 lb.
00680-038	0.50" to 0.74"	24"	5,800 lb.	0.4 lb.
00680-050	0.75" to 1.12"	24"	6,700 lb.	0.5 lb.
00680-100	1.13" to 1.49"	24"	10,000 lb.	0.6 lb.
00680-125	1.50" to 1.99"	24"	16,400 lb.	1.3 lb.
00680-200	2.00" to 2.49"	24"	18,500 lb.	1.5 lb.
00680-250	2.50" to 2.99"	36"	24,500 lb.	2.5 lb.
00680-300	3.00" to 3.74"	36"	24,500 lb.	2.7 lb.
00680-350	3.75" to 4.24"	42"	31,000 lb.	4.2 lb.
00680-400	4.25" to 4.99"	48"	31,000 lb.	4.9 lb.



Always read Breaking Strength, safety and technical data information.

Web Site: www.dcdesign.com
E-mail: sales@dcdesign.com

Toll Free: 1-888-SWIVELS (794-8357)
Tel: 604-232-4445
Fax: 604-232-4446

PULLING & SUPPORT GRIPS

DCD