

MIGHTY - EYE 00760 series


This re-useable Stainless Steel Pulling Eye is specifically designed for pulling Fiber Optic cable with a *single, central, dielectric* strength member.

Specially designed brass collets grip the central strength member and, if required, the kevlar yarn, while a tapered female thread grips the cable jacket. This way all parts of the cable are pulled simultaneously and the fibers get maximum protection.

Keep in mind that single use crimp-on types are also available but are not listed in this catalog, please contact customer service for more information.

When ordering:

From Table A match the 'cable diameter' range with the cable to be used and select the corresponding part number.



Part No.	Cable Diameter		Weight
	Min.	Max.	
00760-009	0.38"	0.44"	0.16 lb.
00760-011	0.44"	0.50"	0.17 lb.
00760-012	0.50"	0.56"	0.29 lb.
00760-014	0.56"	0.62"	0.29 lb.
00760-015	0.62"	0.68"	0.39 lb.
00760-017	0.68"	0.74"	0.39 lb.
00760-019	0.74"	0.81"	0.42 lb.
00760-020	0.81"	0.85"	0.42 lb.
00760-022	0.85"	0.91"	0.49 lb.
00760-023	0.91"	0.97"	0.49 lb.
00760-025	0.97"	1.03"	0.55 lb.
00760-026	1.03"	1.10"	0.55 lb.

Using Table B match the diameter of the dielectric central strength member and select the corresponding collet kit part number.

Part No.	Strength Member Dia.		Weight
	Min.	Max.	
00705-019	0.078"	0.092"	0.34 lb.
00705-023	0.093"	0.108"	0.33 lb.
00705-027	0.109"	0.124"	0.33 lb.
00705-031	0.125"	0.139"	0.32 lb.
00705-035	0.140"	0.155"	0.32 lb.
00705-039	0.156"	0.170"	0.30 lb.
00705-043	0.171"	0.186"	0.29 lb.
00705-047	0.187"	0.202"	0.26 lb.


THIS ITEM IS NOT SUPPLIED WITH COLLETS.
THESE MUST BE ORDERED SEPARATELY TO SUIT APPLICATION.

MIGHTY - EYE 00770 series

This re-useable Stainless Steel Pulling Eye is specifically designed for pulling Fiber Optic cable with a *single, central, steel* strength member.

Specially designed so that three set screws can grip the steel strength member while a tapered female thread grips the cable jacket. This way all parts of the cable are pulled simultaneously and the fibers get maximum protection.

Keep in mind that the single use crimp-on types are also available, please contact customer service for more information.



Part No.	Cable Diameter		Weight
	Min.	Max.	
00770-009	0.38"	0.44"	0.19 lb.
00770-011	0.44"	0.50"	0.19 lb.
00770-012	0.50"	0.56"	0.21 lb.
00770-014	0.56"	0.62"	0.27 lb.
00770-015	0.62"	0.68"	0.38 lb.
00770-017	0.68"	0.74"	0.50 lb.
00770-019	0.74"	0.81"	0.70 lb.
00770-020	0.81"	0.85"	0.85 lb.
00770-022	0.85"	0.91"	0.85 lb.
00770-023	0.91"	0.97"	0.84 lb.
00770-025	0.97"	1.03"	0.92 lb.
00770-026	1.03"	1.10"	0.91 lb.

Note:

DCD recommends the use of a Breakaway Swivel, series 00550, with these products in order to ensure there is no damage to the fibers during installation.

Web Site: www.dcdesign.com
E-mail: sales@dcdesign.com

Toll Free: 1-888-SWIVELS (794-8357)
Tel: 604-232-4445
Fax: 604-232-4446

CABLE PULLING EYES

DCD