

## SPOOL FRAME 58540 series

The DCD Spool Frame is engineered for years of trouble free usage. While DCD offers this product for carrying our Pull Tapes, it can also be used for carrying data and communication cable drums. It has an easy fold up frame that is convenient for carrying or storage and does not require removing the spool or the spool support bar.



Part No.	Description	Weight
58540-010	Spool Frame	8.0 lbs.

## TAPES AND TWINE 58500 series

DCD has now partnered with A-D Technologies (Arnco) in handling a wide range of high performance Bull-Line™ Pull Tape products to expedite cable installation. Choose from woven polyester tape products which are available in a variety of strengths and lengths. A single pull tape eliminates the additional labor required for string, rope or winch line combinations. All Bull-Line™ tape is manufactured with the Stiff-Tape™ lubrication coating, resulting in the highest performance pull tape available in the industry. Whatever the choice, Bull-Line™ Pull Tapes have continually provided a superior alternative to plastic pull ropes in cable installations through all types of conduit. A-D Technologies Bull-Line™ Pull Tapes meet or exceed all pull line requirements of Bellcore GR-356-CORE. Polyester Bull-Line™ is the most economical pull tape, very strong and durable and the elongation at yield is about 12 to 15%. Detectable tapes have a 22 gauge solid copper wire woven into the tape.



Part No.	Description	Tensile Strength	Weight
58500-530	PULL TAPE-PRELUBRICATED - 1/2" x 3,000 ft	1,250 lb.	21 lb.
58500-630	PULL TAPE-PRELUBRICATED - 5/8" x 3,000 ft	1,800 lb.	35 lb.
58500-665	PULL TAPE-PRELUBRICATED - 5/8" x 6,560 ft (2000 m)	1,800 lb.	80 lb.
58500-730	PULL TAPE-PRELUBRICATED - 7/8" x 3,000 ft	2,500 lb.	50 lb.
58500-765	PULL TAPE-PRELUBRICATED - 7/8" x 6,560 ft (2000 m)	2,500 lb.	109 lb.
58510-550	DETECTABLE PULL TAPE - 1/2" x 5,000 ft	1,250 lb.	46 lb.
58510-650	DETECTABLE PULL TAPE - 5/8" x 5,000 ft	1,800 lb.	62 lb.
58520-001	MEASURING TAPE - 3/16" x 3,000 ft	160 lb	4.2 lb.
58530-001	BLOWING TWINE c/w PAIL AND LID - 7,000 ft	180 lb	12 lb.
58530-002	BLOWING TWINE c/w PAIL AND LID - 3,000 ft	400 lb	12 lb.