

LASHING WIRE CLAMPS 61090 series

DCD Lashing Wire Clamps are furnished with double ended stud bolt and washers and free running nuts, all galvanized. Non metallic type clamps are also available but be sure to specify strand diameter.



Part No.	Model	Strand Size	Type	Clamps/box	Weight
61090-001	D-901	.250"/.437"	Two Piece	100	11 lb.
61090-002	E-902	.250"/.375"	One Piece	100	11 lb.
61091-228	NM-LC5-1	.228"/.256"	Non-metallic	100	5 lb.
61091-307	NM-LC5-1.5	.307"/.342"	Non-metallic	100	5 lb.
61091-351	NM-LC5-2	.351"/.394"	Non-metallic	100	5 lb.
61091-404	NM-LC5-4	.404"/.452"	Non-metallic	100	5 lb.
61091-449	NM-LC5-6	.449"/.511"	Non-metallic	100	5 lb.
61091-453	NM-LC5-7	.453"/.546"	Non-metallic	100	5 lb.
61091-513	NM-LC5-8	.513"/.586"	Non-metallic	100	5 lb.

TEMPORARY LASHING WIRE CLAMPS 62560 series

Use the 62560-000 to temporarily secure lashing wire to a termination point in mid-span or at a pole. This clamp is machined from solid cold drawn brass with a plated screw to eliminate corrosion if inadvertently left on strand for an extended period. This clamp assures maximum in-field life.



Part No.	Model	Dimensions	Weight
62560-000	LC5	4" X 2" X 2"	3/4 lb.

Web Site: www.dcdesign.com
E-mail: sales@dcdesign.com

Toll Free: 1-888-SWIVELS (794-8357)
Tel: 604-232-4445
Fax: 604-232-4446

OVERHEAD PRODUCTS

DCD